

LED GU10 10W PREMIUM ceramic



| | | | |
|-----------------|----------------------|--------------------|---------------|
| Power | 10 W | Voltage | 230 V |
| Luminous flux** | 910 lm (360°) | Colour temperature | 3000 K |
| Colour of light | WW | Beam angle | 110 ° |
| Socket | GU10 | | |



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|-----------------|
| Code | WOJ+14308 |
| Power | 10 W |
| Nominal current | 80 mA |
| Voltage | 230 V |
| Energy efficiency class | F |
| Energy consumption | 10 kWh/1000h |
| Frequency | 50HZ Hz |
| Power factor | 0.5 |
| Useful luminous flux* | 830 lm (120°) |
| Luminous flux** | 910 lm (360°) |
| Lamp efficacy | 91 lm/W |
| Luminous intensity | 280 cd |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 110 ° |
| RA | 82 |
| Uniformity of color SDCM max | 5 |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Socket | GU10 |
| Colour | White |
| Dimension (AxBxC) | 50x56 mm |
| Weight | 0.06 kg |
| For use | Inside |
| Application | INT |
| Made in | PRC |
| Other | PREMIUM QUALITY |

